
ALTITUDE



TECHNICAL SPECIFICATIONS

Product Range	Altitude
Product Description	Tufted Multi-Level Loop Carpet Tile
Yarn / Fibre	100% Solution Dyed Nylon 6
Machine Gauge	1/12th
Pile Height	4.0mm +/-0.5mm
Total Thickness	7.0mm +/-0.5mm
Tile Size	50cm x 50cm
Backing Structure	PVC with Recycled Content
Installation Method	Quarter Turn, Ashlar, Brick

SUSTAINABILITY SPECIFICATIONS

Less Waste	Modular carpet creates 85 – 90% less waste than broadloom carpet
Product Stewardship	100% take back & repurpose through accredited partner
Recycled Content	Minimum of 55% recycled content in the backing structure
	Average of 40% recycled content by weight of product
Accreditation	Carpet & Rug Institute Green Plus (CRI Green Plus)
	EU CE Accreditation ISO14001:2004 Environment Certification Syste ISO9001:2008 Quality System Certificate

PERFORMANCE SPECIFICATIONS

Area of Use Dimensional Stability Biocontaminant Control Anti-Static Warranty Commercial Less than 0.2% variation Ultra Fresh Anti-microbial treated AATCC134 < 3000 Volts To be installed according to Australian Standards AS/NZS 2455:1:2007 and AS/NZS 2455.2:2007.

15 year limited warranty:

- Manufacturing defect
- Dimensional stability
- Electrostatic propensity





Specifications are subject to manufacturing tolerances and may be changed without notice. Colour variation may occur between sample and supplied products due to dye lot tolerances.



AIRLAY FLOORCOVERINGS

Head Office: 91-115 Link Drive, Campbellfield VIC 3061 Phone: (03) 9359 4705 Email: sales@airlay.com.au