

# DYNAMIC



**Bold**



**Drive**



**Lively**

## TECHNICAL SPECIFICATIONS


<b>Product Range</b>	Dynamic
<b>Product Description</b>	Tufted Multi-Level Loop Carpet Tile
<b>Yarn / Fibre</b>	100% Solution Dyed Nylon
<b>Machine Gauge</b>	1/12th
<b>Pile Height</b>	4.0mm +/-0.5mm
<b>Total Thickness</b>	7.0mm +/-0.5mm
<b>Tile Size</b>	50cm x 50cm
<b>Backing Structure</b>	PVC with Recycled Content / Felt Backing
<b>Installation Method</b>	Quarter Turn, Ashlar, Brick

## SUSTAINABILITY SPECIFICATIONS

<b>Less Waste</b>	Modular carpet creates 85 – 90% less waste than broadloom carpet
<b>Product Stewardship</b>	100% take back & repurpose through accredited partner
<b>Recycled Content</b>	Minimum of 55% recycled content in the backing structure  Average of 40% recycled content by weight of product
<b>Accreditation</b>	Carpet & Rug Institute Green Plus (CRI Green Plus) EU CE Accreditation ISO14001:2004 Environment Certification System ISO9001:2008 Quality System Certificate

## PERFORMANCE SPECIFICATIONS

<b>Area of Use</b>	Commercial
<b>Dimensional Stability</b>	Less than 0.2% variation
<b>Biocontaminant Control</b>	Ultra Fresh Anti-microbial treated
<b>Anti-Static</b>	AATCC134 < 3000 Volts
<b>Warranty</b>	To be installed according to Australian Standards AS/NZS 2455.1:2007 and AS/NZS 2455.2:2007.  15 year limited warranty: • Manufacturing defect • Dimensional stability • Electrostatic propensity



Specifications are subject to manufacturing tolerances and may be changed without notice. Colour variation may occur between sample and supplied products due to dye lot tolerances.

AIRLAY 

[WWW.AIRLAY.COM.AU](http://WWW.AIRLAY.COM.AU)

## AIRLAY FLOORCOVERINGS

**Head Office:** 91-115 Link Drive, Campbellfield VIC 3061

**Phone:** (03) 9359 4705 **Email:** sales@airlay.com.au