

GEOFORM



TECHNICAL SPECIFICATIONS

Product Range Geoform

Product Description Structured Loop Carpet Plank
Yarn / Fibre 100% Solution Dyed Nylon

Machine Gauge 1/12th

 Pile Height
 2.5mm +/-0.5mm

 Total Thickness
 5.0mm +/-0.5mm

 Tile Size
 25cm x 100cm

Backing StructurePVC with Recycled ContentInstallation MethodHerringbone, Ashlar, Brick

SUSTAINABILITY SPECIFICATIONS

Less Waste Modular carpet creates 85 – 90% less

waste than broadloom carpet

Product Stewardship 100% take back & repurpose through

accredited partner

Recycled Content Minimum of 55% recycled content in

the backing structure

Average of 40% recycled content by

weight of product

Accreditation Carpet Institute of Australia ECS4

Carpet & Rug Institute Green Plus (CRI Green Plus)

EU CE Accreditation

ISO14001:2004 Environment Certification System ISO9001:2008 Quality System Certificate

PERFORMANCE SPECIFICATIONS

Area of Use

Dimensional Stability

Biocontaminant Control

Anti-Static

Warranty

Commercial

Less than 0.2% variation

Ultra Fresh Anti-microbial treated

AATCC134 < 3500 Volts

To be installed according to Australian Standards

AS/NZS 2455:1:2007 and AS/NZS 2455.2:2007.

15 year limited warranty:

- Manufacturing defect
- Dimensional stability
- Electrostatic propensity













Specifications are subject to manufacturing tolerances and may be changed without notice. Colour variation may occur between sample and supplied products due to dye lot tolerances.



AIRLAY FLOORCOVERINGS

Head Office: 91-115 Link Drive, Campbellfield VIC 3061 **Phone:** (03) 9359 4705 **Email:** sales@airlay.com.au