

COMO



Armada



Surrey Hills



Hampton

TECHNICAL SPECIFICATIONS


Product Range	Como
Product Description	Tufted Multi-Level Loop Carpet Tile
Yarn / Fibre	100% Solution Dyed Nylon
Machine Gauge	1/12th
Pile Height	3.0mm +/-0.5mm
Total Thickness	7.0mm +/-0.5mm
Tile Size	50cm x 50cm
Backing Structure	PVC with Recycled Content or Cushion Back
Installation Method	Quarter Turn, Ashlar, Brick

SUSTAINABILITY SPECIFICATIONS

Less Waste	Modular carpet creates 85 – 90% less waste than broadloom carpet
Product Stewardship	100% take back & repurpose through accredited partner
Recycled Content	Minimum of 55% recycled content in the backing structure Average of 40% recycled content by weight of product
Accreditation	Carpet Institute of Australia ECS4 Carpet & Rug Institute Green Plus (CRI Green Plus) EU CE Accreditation ISO14001:2004 Environment Certification System ISO9001:2008 Quality System Certificate

PERFORMANCE SPECIFICATIONS

Area of Use	Commercial
Dimensional Stability	Less than 0.2% variation
Biocontaminant Control	Ultra Fresh Anti-microbial treated
Anti-Static	AATCC134 < 3000 Volts
Warranty	To be installed according to Australian Standards AS/NZS 2455.1:2007 and AS/NZS 2455.2:2007. 15 year limited warranty: • Manufacturing defect • Dimensional stability • Electrostatic propensity



Specifications are subject to manufacturing tolerances and may be changed without notice. Colour variation may occur between sample and supplied products due to dye lot tolerances.