

## **CORPORATE**

### **Technical Specifications**

<b>PRODUCT RANGE</b>	CORPORATE
<b>PRODUCT DESCRIPTION</b>	Tufted Textured Loop Carpet Tile
<b>YARN / FIBRE</b>	100% Solution Dyed Nylon
<b>MACHINE GAUGE</b>	1/10 <sup>th</sup> & 1/12 <sup>th</sup> GAUGE
<b>PILE HEIGHT</b>	3.5 mm +/-0.5mm
<b>TOTAL THICKNESS</b>	6.5 mm +/-0.5mm
<b>TILE SIZE</b>	50cm x 50cm
<b>BACKING STRUCTURE</b>	PVC with Recycled Content
<b>TILE INSTALLATION METHOD</b>	Quarter Turn, Ashlar, Brick

### **Performance Specifications**

<b>AREA OF USE</b>	Commercial
<b>DIMENSIONAL STABILITY</b>	Less than 0.2% variation
<b>BIOCONTAMINANT CONTROL</b>	Ultra Fresh Anti-microbial treated
<b>ANTI-STATIC</b>	AATCC134 ≤ 3500 Volts
<b>WARRANTY</b>	To be installed according to Australian Standards AS/NZS 2455:1:2007 and AS/NZS 2455.2:2007.
	15 year limited warranty: <ul style="list-style-type: none"> <li>• Manufacturing defect</li> <li>• Dimensional stability</li> <li>• Electrostatic propensity</li> </ul>

### **Sustainability Specifications**

<b>LESS WASTE</b>	Modular carpet creates 85 – 90% less waste than broadloom carpet
<b>RECYCLABLE/PRODUCT STEWARDSHIP</b>	100% take back and repurpose through accredited partner
<b>RECYCLED CONTENT</b>	Minimum of 55% recycled content in the backing structure Average of 40% recycled content by weight of product Carpet and Rug Institute Green Plus (CRI Green Plus)
<b>ACCREDITATION</b>	EU CE Accreditation ISO14001:2004 Environment Certification System ISO9001:2008 Quality System Certificate

**[www.airlay.com.au](http://www.airlay.com.au)**