

# LAKESIDE

## TECHNICAL SPECIFICATIONS

<b>Flooring Type</b>	Multi-Level Loop Pile Carpet Tiles
<b>Yarn / Fibre</b>	100% Solution Dyed Nylon
<b>Machine Gauge</b>	1/12th
<b>Pile Height</b>	3.0mm +/-0.5mm
<b>Overall Thickness</b>	PVC: 5.0mm +/-0.5mm / Cushion: 8.0mm +/-0.5mm
<b>Plank Size</b>	50cm x 50cm
<b>Backing Structure</b>	PVC Backing: Recycled Content / Cushion Backing: PET
<b>Installation Method</b>	Quarter Turn, Ashlar, Brick


## SUSTAINABILITY SPECIFICATIONS

<b>Less Waste</b>	Modular carpet creates 85 – 90% less waste than broadloom carpet
<b>Product Stewardship</b>	100% take back & repurpose through accredited partner
<b>Recycled Content</b>	Minimum of 55% recycled content in the backing structure Average of 40% recycled content by weight of product
<b>Accreditation</b>	Carpet Institute of Australia ECS4 Carpet & Rug Institute Green Plus (CRI Green Plus) EU CE Accreditation ISO14001:2004 Environment Certification System ISO9001:2008 Quality System Certificate

## PERFORMANCE SPECIFICATIONS

<b>Classification (use area)</b>	Commercial
<b>Dimensional Stability</b>	Less than 0.2% variation
<b>Biocontaminant Control</b>	Ultra Fresh Anti-microbial treated
<b>Anti-Static</b>	AATCC134 < 3500 Volts
<b>Warranty</b>	To be installed according to Australian Standards AS/NZS 2455.1:2019 and AS/NZS 2455.2:2019. 15 year warranty: <ul style="list-style-type: none"> <li>• Manufacturing defect</li> <li>• Dimensional stability</li> <li>• Electrostatic propensity</li> </ul>

Specifications are subject to manufacturing tolerances and may be changed without notice.  
Colour variation may occur between sample and supplied products due to dye lot tolerances.



Crimson & Powder



Ink