

ALPINE ARTISAN

DESCRIPTION

Luxury Vinyl Tiles	EN649/EN ISO 10582	—	Heterogeneous PVC
Overall Thickness	EN428/ISO 24346	mm	3.00
Wear Layer Thickness	EN429/ISO 24340	mm	0.55 (±0.05)
Tile Size 1	EN 427/ISO 24342	mm	500x500
Tiles/Meterage per box			13 pcs, 3.25m ² /box
Tile Size 2	EN 427/ISO 24342	mm	600x600
Tiles/Meterage per box			9 pcs, 3.24m ² /box

CLASSIFICATION

Classification	EN685/ISO 10874	class	Commercial: 33 Industrial: 42
Fire Rating	AS ISO 9239-1	—	≥8 kW/m ²
Slip Resistance	AS 4586	—	R10
	DIN 51130	class	R10

PERFORMANCE

Abrasion Resistance	EN660-2	—	Group T
Dimensional Stability	EN434/ISO 23999	%	≤ 0.25%
Residual Indentation	EN433/ISO 24343:1	mm	Ave. Value ≤ 0.1mm
Electrical Resistance	EN 1815	kv	<2kv
	EN 1081	—	>10 ⁹ Ω
Colour Fastness	EN ISO - 105 - B02	degree	≥6 degree
Chemical Resistance	EN 423/ISO 26987	—	Good Resistance
Castor Wheel Test	EN 425/ISO 4918	—	Suitable

ENVIRONMENTAL

Underfloor Heating	—	°C	Suitable - Max. 27°C
VOC Emissions	Floor Score/SCS SCS-EC10.3-2014v4.0		Indoor Airway Quality Certified Pass, Low VOC Emissions
Quality Control	ISO 9001:2000	certified	
Management	ISO 14001:2004	certified	

Specifications are subject to manufacturing tolerances and may be changed without notice. Colour variation may occur between sample and supplied products due to dye lot tolerances.



AIRLAY

WWW.AIRLAY.COM.AU

AIRLAY FLOORCOVERINGS

Head Office: 25-27 Lakeside Drive Broadmeadows, VIC 3047
Phone: (03) 9359 4705 Email: sales@airlay.com.au