

NOVALIS®

AIRLAY
floorcoverings

Novafloor 2,5/0,55

Heterogenous Luxury Vinyl Tile EN 649

Properties	Standard	Unit	Plank/Wood Designs	Tile/Stone Designs		
Technical specification						
Size Planks	 EN 427	mm	a.) 914,4 x 152,4 b.) 1219,2 x 127,0 c.) 1219,2 x 177,8 d.) 1219,2 x 228,6	a.) 406,4 x 406,4 b.) 457,2 x 457,2 c.) 609,6 x 304,8		
Thickness	 EN 428	mm	2,5			
Wearlayer	EN 429	mm	0,55			
Weight per sqm	 EN 430	g/m ²	4310			
Performance						
Classification	EN 685	Class				
Fire Classification	EN 13501-1	Class				
Slipresistance	EN 13893 DIN 51130	Class	 R10			
Weargroup	EN 660-1	-	T			
Residual Indentation	EN 433	mm	 <0,1 mm			
Thermal Conductivity	DIN 52612		0,02 m ² k/w			
Electrical Conductivity	EN 1081	Ohm	 ≤10 ⁹ Ω ≤10 ⁹ Ohm			
Castor Chair	EN 425		Yes, Type W			
Light fastness	ISO 105-B02	Degree	 m> 6 Grade			
Sound absorption	EN 140-8	dB	approx. 3			
Chemical resistance	EN 423		 Yes			
Floor heating system		Degree	Yes, max. 27C°			
CE Marking	EN 14041		 EN 14041: 2011			
Other	PCP under detection limit  Formaldehyde has not been added					
Document: TDS Version: 01.04.2014 Superseeds: 02.12.2013 Created: DR Approved: CR Processed to CSD: by	 					

Novafloor 2,5/0,55

Heterogenous Luxury Vinyl Tile EN 649

Logistical Data Sheet

Pieces per box		piece	a.) 24 b.) 21 c.) 15 d.) 12	a.) 20 b.) 16 c.) 18
Sqm per box		sqm	a.) 3,345 b.) 3,252 c.) 3,252 d.) 3,345	a.) 3,303 b.) 3,345 c.) 3,345
Boxes per pallet		Piece	a.) 50 b.) 70 c.) 70 d.) 68	a.) 52 b.) 64 c.) 66
Sqm per pallet		sqm	a.) 167,23 b.) 227,61 c.) 227,61 d.) 227,43	a.) 171,77 b.) 214,05 c.) 220,74
Pallet's per Container		Piece	a.) 24 b.) 18 c.) 18 d.) 18	a.) 24 b.) 20 c.) 18

Document: LDS
Version: 02.12.2013
Superseeds: all older Versions
Created: DR
Approved: CR
Processed to CSD: by