

MARBLE EFFECTS

HOMOGENEOUS PUR

DESCRIPTION

Type of Floor Covering	EN ISO 10581	–	Homogeneous
Overall Thickness	EN 428	mm	2.00
Wear Layer Thickness	EN 429	mm	2.00
Total Weight	EN 430	g/m ²	3300 g/m ²
Roll Dimensions	EN 426	m ²	2.0 x 20m = 40m ²


CLASSIFICATION

Classification	EN 685	class	Commercial: 34 Industrial: 43
Fire Rating	AS ISO 13501-1	–	Class Bfl-S1
	AS ISO 11925-2	–	Pass
	AS ISO 9239-1	–	≥8 kW/m ²
VOC Emissions	ISO 16000	–	Pass
Electrical Resistance	EN 1815	kv	<2kv
	EN 1081	–	>10 °Ω
Slip Resistance	AS 4586	–	P3
	DIN 51130	–	R10

PERFORMANCE

Abrasion Resistance	EN 649	–	Group P
Dimensional Stability	EN 434	%	≤ 0.40%
Residual Indentation	EN 433	mm	Ave. Value ≤ 0.1mm
Colour Fastness	EN ISO - 105 - B02	degree	≥6 degree
Chemical Resistance	EN 423	–	Good Resistance
Castor Wheel Test	EN 425	–	Suitable
Flexibility	EN 435	–	Excellent
Anti-bacterial and fungicidal	MRSA	–	Good
	DIN EN ISO 846 - A/C	–	Good
Underfloor Heating	–	°C	Suitable - Max. 27°C
Surface Treatment	–	–	PUR

Specifications are subject to manufacturing tolerances and may be changed without notice.
Colour variation may occur between sample and supplied products due to dye lot tolerances.



AIRLAY 

AIRLAY FLOORCOVERINGS

Head Office: 91-115 Link Drive, Campbellfield VIC 3061

Phone: (03) 9359 4705 Email: sales@airlay.com.au

AIRLAY.COM.AU