

# OAKWOOD

## TECHNICAL SPECIFICATIONS

|                                     |                                        |                                            |
|-------------------------------------|----------------------------------------|--------------------------------------------|
| <b>Flooring Type</b>                | Luxury Vinyl Plank                     |                                            |
| <b>Warranty*</b>                    | Residential 25 yrs   Commercial 15 yrs |                                            |
| <b>Plank Size</b>                   | ISO 24342 (EN 427)                     | 8 @ 1524 X 230mm = 2.80m <sup>2</sup> /box |
| <b>Overall Thickness</b>            | ISO 24346 (EN 428)                     | 5.0mm                                      |
| <b>Wear Layer</b>                   | ISO 24340 (EN 429)                     | 0.50mm                                     |
| <b>Total Weight</b>                 | ISO 23997 (EN 430)                     | 27.2kg                                     |
| <b>Surface Treatment</b>            | PUR                                    |                                            |
| <b>Classification (use area)</b>    | ISO 10874 (EN 685)                     | 33, 42                                     |
| <b>General Performance</b>          | ISO 10582 (EN 649)                     | Conforms                                   |
| <b>Reaction to fire</b>             | EN 13501-1<br>AS ISO 9239.1            | Class Bfl-S1<br>≥8kW/m <sup>2</sup>        |
| <b>Slip Resistance</b>              | DIN 51130<br>AS 4586<br>EN 13893       | R10<br>P3<br>Class DS                      |
| <b>Static Electrical Propensity</b> | EN 1815                                | ≤ 2.0kV                                    |
| <b>Abrasion Resistance</b>          | EN 660-2                               | Group T                                    |
| <b>Residual Indentation</b>         | ISO 24343-1 (EN 433)                   | <0.1mm                                     |
| <b>Dimensional Stability</b>        | ISO 23999 (EN 434)                     | ≤ 0.25%                                    |
| <b>Castor Chair</b>                 | ISO 4918 (EN 425)                      | Suitable - Type W                          |
| <b>Colour Fastness</b>              | ISO 105-B02                            | Method 3 ≥ 6                               |
| <b>Underfloor Heating</b>           | Suitable - max 27°C                    |                                            |
| <b>VOC Emissions</b>                | Indoor Air Quality<br>FloorScore       | Very low emissions<br>Certified            |

Specifications are subject to manufacturing tolerances and may be changed without notice. Colour variation may occur between sample and supplied products due to dye lot tolerances.

### \*Warranty

The flooring has a 15 year commercial and 25 year residential warranty for latent manufacturing defects. The warranty is subject to the products being specified, installed and maintained in accordance with our recommendations (instructions available on request).



RESIDENTIAL  
WARRANTY



COMMERCIAL  
WARRANTY



WATER  
RESISTANT



OAK GRAIN  
TOUCH



CERTIFIED  
9001



CERTIFIED  
14001



Nero Oak



Grey Oak



Husk Oak